



# MODEL 6002, 6002-14B, 6002A, and 6002-14A

## Ventilation Gas Detectors



### APPLICATIONS:

Vehicle Emissions | Combustible Gases | Refrigeration Gas  
Leak Detection | Industrial Health and Safety

## ELIMINATE CO and NO<sub>2</sub> EASILY WHEN IT MATTERS

### FEATURES

These gas detectors turn on, off, or adjust speed depending on the amount of gas present. Detection levels are easily set to trigger the system as needed to maintain code and save money. Zones can be established so only the fans needed are adjusted.

- Stand-alone operation with 1 or 2 adjustable alarm relays, indicators and strobe
- 6002-A and 6002-14A have 1 relay and accept 4-20mA or 2-10V signals from VFDs or ECMs for speed control
- BTL listed Smart Sensor
- BACnet MS/TP RS485 interface
- CAN network interface for master-slave operation or central control
- Pre-calibrated plug-and-play sensor modules
- Impact resistant water resistant enclosure

### COMPATIBLE WITH S&P USA PRODUCTS:

- **Jet Fan Series (IFFT, TJFU, IFAB, and IFEB)** - Centrifugal and Axial Jet Fans
- **GED/GSD** - Direct Drive Sidewall Propeller Exhaust/Supply Fans
- **eGED/eGSD** - Direct Drive Sidewall Propeller Exhaust/Supply Fans
- **LC** - Belt Drive Sidewall Propeller Exhaust/Supply Fans
- **CM** - Belt Drive Utility Vent Set
- **L2 & L3** - Belt Drive Sidewall Propeller Exhaust/Supply Fans
- **S-Series Fans (SDB, STXB, SDBD, and STXD)** - Centrifugal Roof & Wall Fans